DRAWING FOR CUSTOMER







■SPEC.:
- ●Rated Voltage: 30V AC,DC
- ●Rated Current: 0.5A
- ●Withstand Voltage: 200V AC/minute
- ●Contact Resistance: 20mΩ max
- ●Insulation Resistance: 100MΩ min
- ●Temperature Range: -25°C~+85°C

■Material:
- ●Insulator(A): LCP UL94V-0
- ●Contact Pin(B): Phosphor Bronze
  Finish:Matted Sn-Plated,over Nickel
- ●Solder Tab(C):Phosphor Bronze
  Finish:Matted Sn-Plated,over Nickel
- ●Cap(D):LCP UL94V-0





PCB LAYOUT



KB802-X X X S V S 6 A

- Pin No.
- P:PE 袋装
- R:REEL 卷装
- T:TUBE 管装
- S:SMT
- D:DIP
- R:Right angle
- V:Verical
- G:GOLD FLASH
- S:MATTE TIN
- Mold No.
- Version

Poles	Dimensions(mm)		Poles	Dimensions(mm)	
	A	B		A	B
02	0.8	3.8	14	10.4	13.4
03	1.6	4.6	15	11.2	14.2
04	2.4	5.4	16	12.0	15.0
05	3.2	6.2	17	12.8	15.8
06	4.0	7.0	18	13.6	16.6
07	4.8	7.8	19	14.4	17.4
08	5.6	8.6	20	15.2	18.2
09	6.4	9.4	21	16.0	19.0
10	7.2	10.2	22	16.8	19.8
11	8.0	11.0	23	17.6	20.6
12	8.8	11.8	24	18.4	21.4
13	9.6	12.6	25	19.2	22.2

XYCO Precision Connectors

XYCO 东莞市轩业电子科技有限公司
TEL: 0769-8297 9981/2/3 http://www.XYCO.com.cn

DATE 日期	VER 版本	CHANGE HISTORY 變更歷史	CHANGED NAME 修改後料號	DRAWING 變更者
2016-11-30	A		KB802-XXXSVS6A	Devin

TOLERANCE 公 差	DRAWING 設計者	Devin	KB802-XXXSVS6A
.X=±0.30 .XX=±0.20 .XXX=±0.10	CHECKED 審查	Thomas	PART NO. 料號
	APPROVED 核准	William	DWG NO. 圖號

UNIT 單位	mm	PRODUCT NAME 產品名稱	SURS PH0.80mm Wire To Board SMT Verical Wafer